











SLIDE VALERIANA



SLIDE VALERIANA is the harvesting machine for corn-salad. The cutting system permits indeed to work on any kind of soil, both on sanded or normal soil. The connecting rod system allows an alternate movement of the blade, assuring a very good cut at the collar level. The cutting height is controlled by a panel control with level indicator. The cut product is forwarded on a vibrating belt, which cleans it from the sand or soil, without overturning or turning it continuously. The belt speed is adjustable. It is possible to start the automatic forward movement with the desired working speed.

MOD.										
	cm/in	cm/in	cm/in	cm/in	HP/KW			km/h	Kg/lb	cm/in
SLIDE VALERIANA	Min. 135/53,1	120 • 130 • 140 • 150 • 160 • 170 • 180/ 47,2 • 51,2 • 55,1 • 59,1 • 63 • 66,9 • 70,9	13/5,1	Max. 24/9,4	MOTORE • ENGINE • MOTEUR • MOTOR • MOTOR KUBOTA V 1505, 4 CILINDRI DIESEL, 24.8 HP/ 18.5 KW	idrostatica hydrostatic hidrostatica idrostatica hydrostatic гидростатический	4	0 - 10	1800/ 3968,3	A: Max.210 B: 550 H: 145 A: Max. 55,1 B: 216,5 H: 57,1