











## SLIDE



SLIDE is an harvesting machine mounted on four driving wheels, optimal to work in greenhouses or open field, also with wet soils. Designed for the baby-leaf-products, SLIDE can be equipped with accessories to put the product direct into the boxes on the field, to unload it into a trailer with a side conveyor, or to transport it till the processing level trough some guiding conveyors. SLIDE is equipped with a steering wheel with hydraulically assisted steering and temporary electric stop device in the forward movement and recovery at the same speed. The blade is turning on self - centering pulleys covered by rubber that improve the blade lasting. It is equipped with a belt cleaning brush. The cutting height is kept by proportional electro - hydraulic sensors that guarantee for a perfect control.

MOD.										
	cm/in	cm/in	cm/in	cm/in	HP/KW			km/h	Kg/lb	cm/in
SLIDE	Min. 135 53,1	120 • 130 140 • 150 • 160 170 • 180 47,2 • 51,2 • 55,1 • 59,1 • 63 • 66,9 • 70,9	23/9,1	Max. 40/ 15,7	MOTORE • ENGINE • MOTEUR • MOTOR • MOTOR KUBOTA V 1505, 4 CILINDRI DIESEL, 24.8 HP/ 18.5 KW	idrostatica hydrostatic hidrostàtica idrostatica hydrostatic гидростатический	4	0 - 10	1600/ 3527,4	A: 550 B: Max. 210 H: 145  A: 216,5 B: Max. 82,7 H: 57,1